Specification

Dual Line

Cloud Managed

Full Color LCD

Real Time Response

7/24 Operating

400cd/m2 Highlight

High-Precision Display

	RLCD0101N	RLCM0101N	RLCD0140N	RLCM0140N
	10.1inch Electronic Shelf Label, LCD Model	10.1inch Electronic Shelf Label, Double Sided LCD Model	14inch Electronic Shelf Label, LCD Model	14inch Electronic Shelf Label, Double Sided LCD Model

DISPLAY FEATURES				
Display Technology	TFT	TFT	TFT	TFT
Active Display Area(mm)	135.36（W）X 216.576（H）mm	135.36（W）X 216.576（H）mm（*2）	173.99 (W) X 309.31 (H) mm	173.99 (W) X 309.31 (H) mm（*2）
Resolution (Pixels)	800X1280	800X1280	1920*1080	1920*1080
Pixel Colors	Full color	Full color	Full color	Full color
Viewing Angle	12 o'clock	12 o'clock	12 o'clock	12 o'clock
Backlight	White hight LED backlight	White hight LED backlight	White hight LED backlight	White hight LED backlight
Brightness	400cd/m2	400cd/m2	280cd/m2	280cd/m2
Usable Pages	6	6	6	6

WIRELESS				
Operating Frequency	2.4-2.485GHz	2.4-2.485GHz	2.4-2.485GHz	2.4-2.485GHz
Encryption	128-bit AES	128-bit AES	128-bit AES	128-bit AES
OTA	YES	YES	YES	YES

PHYSICAL FEATURES				
Powered by	DC powered	DC powered	DC powered	DC powered
NFC	YES	YES	YES	YES
Operating Temperature	25±5 ℃	25±5 ℃	-20-50 ℃	-20-50 ℃
Dimensions	243.2*152*14mm	243*150.1*14mm	333*202.3*14.5mm	333*202.3*14.5mm

COMPLIANCE				
Certification	CE,ROHS,FCC,MIC	CE,ROHS,FCC,MIC	CE,ROHS,FCC,MIC	CE,ROHS,FCC,MIC