



Q SERIES KIOSK

Active Series


Create Impressive Space for all Target Audience

Promote your corporate image with such detail and excellent visibility

Unisign Kiosk is a good connection way between the target audience and your brand. It helps that you draw visitors attention and deliver messages more effectively with stunning visibility. Also it supports sharing rich visual contents, advertisement and information about anything you want.



Elegant Design



Manage Contents



24/7 working



Energy efficient technology



Superior visibility and high brightness



Anti-vandal protective glass

Present strikingly messaging with new generation digital solutions

Unisign Kiosks enable interaction with multimedia content, maps, information, advertising posters, websites, video and more for you can contact with any audiences anywhere. It enables interaction with multimedia content, maps, information, advertising posters, websites, videos and more.



Built-in WIFI

As well as having and LAN ports you can wirelessly connect to the internet with built in WIFI.

Touch Technology

The most popular interactive applications durable and reliable touch technology for ease of use.

Branding and Color Applications

Provides you to highlight your corporate identity with unique color and logo application.

Application Specific Design

Depending on where you are positioning, special foot design can be made.

Front Protection Glass

It is manufactured from glass that is reinforced by chemical processes and is resistant to very high piercing. Provides additional protection against physical impact during use.

Long Life Industrial Design

Designed for use in commercial applications this screen can run 24/7. There are no external buttons or controls to avoid tampering.

Rich Entegration System

It has the infrastructure that can work seamlessly with Windows and Android platforms.

Audio

Optional integrated speaker also has an audio out port for connecting headphones or external speakers.

PANEL	KS121EA-QP	KS150EA-QP	KS170EA-QP	KS185EA-QP	KS215EA-QP
Panel Size	12,1"	15"	17"	18,5"	21,5"
Panel Type	60Hz ELED	60Hz ELED	60Hz ELED	60Hz ELED	60Hz ELED
Resolution	1024 X 768	1024 X 768	1280 X 1024	1920 X 1080	1920 X 1080
Brightness (Typ.)	350 cd/m ²	350 cd/m ²	350 cd/m ²	350 cd/m ²	350 cd/m ²
Contrast	1300:1 (Typ.) (TM)	1300:1 (Typ.) (TM)	1300:1 (Typ.) (TM)	1300:1 (Typ.) (TM)	1300:1 (Typ.) (TM)
Viewing Angle (H x V)	170° x 170°	170° x 170°	170° x 170°	170° x 170°	170° x 170°
Response Angle (G-to-G)	16 ms (G to G)	16 ms (G to G)	16 ms (G to G)	16 ms (G to G)	16 ms (G to G)
Active Display Area (mm)	243.36 (H) x 184.32 (V)	304.2 (H) x 228.3 (V)	342 (H) x 274 (V)	410 (H) x 231 (V)	476,64(H) x 268,11(V)
Touch Type	PCAP - 2 Point	PCAP - 2 Point	PCAP - 2 Point	PCAP - 2 Point	PCAP - 2 Point

PANEL CONNECTIVITY

Video Input	VGA, HDMI, DVI	VGA, HDMI, DVI	VGA, HDMI, DVI	VGA, HDMI, DVI	VGA, HDMI, DVI
Video Output	N/A	N/A	N/A	N/A	N/A
Audio Input / Output	Stereo mini Jack	Stereo mini Jack	Stereo mini Jack	Stereo mini Jack	Stereo mini Jack
USB	N/A	N/A	N/A	N/A	N/A
Internal Control	N/A	N/A	N/A	N/A	N/A

POWER

Power Type	Adapter	Adapter	Adapter	Adapter	Adapter
Power Requirement	AC 100 - 240 V- (+/- 10 %), 50/60 Hz	AC 100 - 240 V- (+/- 10 %), 50/60 Hz	AC 100 - 240 V- (+/- 10 %), 50/60 Hz	AC 100 - 240 V- (+/- 10 %), 50/60 Hz	AC 100 - 240 V- (+/- 10 %), 50/60 Hz
Power Consumption	22W	27W	27W	42W	49W
Standby Mode	<0,5W	<0,5W	<0,5W	<0,5W	<0,5W

DIMENSIONS

Product Size(mm) (w x h x d)	500 x 1300 x 350	550 x 1300 x 350	600 x 1450 x 400	650 x 1450 x 400	740 x 1485 x 425
Package Size (mm)	550 x 1400 x 400	600 x 1400 x 400	650 x 1550 x 450	730 x 1550 x 450	800 x 1600 x 475
Product Weight(kg)	32	36	40	40	42
Package Weight(kg)	40	44	48	48	50

OPERATION

Operation Life	7/24 - 50.000 hours	7/24 - 50.000 hours	7/24 - 50.000 hours	7/24 - 50.000 hours	7/24 - 50.000 hours
Working Conditions	Operation Temp.:0~ 40 °C ; Storage Temp.: -20~60 °C	Operation Temp.:0~ 40 °C ; Storage Temp.: -20~60 °C	Operation Temp.:0~ 40 °C ; Storage Temp.: -20~60 °C	Operation Temp.:0~ 40 °C ; Storage Temp.: -20~60 °C	Operation Temp.:0~ 40 °C ; Storage Temp.: -20~60 °C
Humidity	10 ~ 80%	10 ~ 80%	10 ~ 80%	10 ~ 80%	10 ~ 80%

CERTIFICATION AND COMPATIBILITY

Safety	EN60950-1	EN60950-1	EN60950-1	EN60950-1	EN60950-1
EMC	Class A	Class A	Class A	Class A	Class A
Environment	ENERGY STAR 6.0 (USA)	ENERGY STAR 6.0 (USA)	ENERGY STAR 6.0 (USA)	ENERGY STAR 6.0 (USA)	ENERGY STAR 6.0 (USA)

OPTIONAL ACCESSORIES

	Barcode, NFC, RFID, Beacon, Bluetooth, Camera, Pin Pad, Industrial Keyboard, Receipt Printer, Audio System, Glass Protector, Mirror Protector, Glass Logo, Colorful Glass
--	---

OTHER

Included in Packet	Easy Installation Guide, Warranty Document, Power Cable (Other Accessories Externally)
--------------------	---

unisign / DISPLAY
TECHNOLOGY



unisigns



unisigns



unisigns



unisign

www.unisign.com.tr

info@unisign.com.tr



Q SERIES KIOSK

Active Series