





DOUBLE SIDED TOTEM

Outdoor Series

Unisign Outdoor Totem has an elegant and stylish casing design. IP65 rated casing protects it from harsh weather conditions and provide excellent quality with industrial grade panels.



Double Sided



Sunlight Readable



Embedded Android OS



Plug & Play Content



High Brightness

The screens with a brightness value of 2500 nit are easily readable even under direct sunlight and the brightness is adjusted according to the light condition to avoid unnecessary energy consumption.

Stainless Steel Body

Unisign Totem has a IP65 class protection body design that has wide humidity range, against dust and weather resistant.

Branding and Color Applications

Provides you to highlight your corporate identity with unique color and logo application.

Rich Entegration System

It has the infrastructure that can work seamlessly with Windows and Android platforms.

Built-in WIFI

As well as having and LAN ports you can wirelessly connect to the internet with built in WIFI.

Front Protection Glass

It is manufactured from glass that is reforced by chemical processes and is resistant to very high piercing. Provides additional protection against physical impact during use.

Long Life Industrial Design

Designed for use in commercial applications this screen can run 24/7. There are no external buttons or controls to avoid tampering.

Audio

Optional integrated speaker also has an audio out port for connecting headphones or external speakers.



TO490XN-DS

PANEL

Panel Size

49" a-Si TFT LCD

Resolution

3840* 2160

Brightness

2500 nits

Active Area

1073.78 (W) * 604.0 (H) mm

Display Mode

Normally Black, ADS

Viewing Angle

178*178

Contrast Ratio

1100:1

Aspect Ratio

16:9

SYSTEM

CPU

RK3288, Quad Core Cortex A17, 1.8G

RAM

2 GB

Internal Memory

16 GB

OS

Android 8.1

NETWORK

WIFI

802.11b/g/n

Ethernet

10M/100M Ethernet

Bluetooth

4.1

INTERFACE

Card Slot

SD Card

USB

USB

USB

USB/OTG

Ethernet

RJ45

MEDIA PLAY

Video Format

MPEG-1, MPEG-2, MPEG-4,
H.263, H.264, VC1, RV, etc.,
Support up to 4K

Audio Format

MP3/WMA/AAC/ etc.

Photo

jpeg, bmp, etc.

Language

Multi-Language

POWER

Type

Internal

Power Requirement

AC 100-240 V (+/- 10%), 50/60 Hz

Power Consumption

600 W (Typ)

unisign / DISPLAY
TECHNOLOGY



unisignds



Unisign Digital Signage



unisignds



unisign

www.unisign.com.tr

hello@unisign.com.tr



DOUBLE SIDED TOTEM
OUTDOOR SERIES