



TOTEM

Elegance P-Series

Create impressive space for all target audience

Indoor

Excellent and Captivating Visibility

The Unisign Indoor P Series boasts high-tech screens to improve picture quality and optimize message distribution for any viewer. These powerful screens include circular polarization technology that removes the blindness of the image caused by polarized sunglasses.



Elegant Design



Manage Contents



24/7 working



Energy efficient technology



Superior visibility and high brightness



Anti-vandal protective glass



Safe Working In All Conditions

Each Unisign P Series is subjected to defensive tests to provide resistance to environmental variables that can interfere with dust, heat, humidity and operations. Draw visitors attention and deliver messages more effectively with stunning visibility. Indoor Totem features 500 nits brightness and 5000:1 contrast ratio for impeccable visibility.

High Brightness and Vibrant Colors

The screens with a brightness value of 500 nits are easily readable even under direct sunlight and the brightness is adjusted according to the light condition to avoid unnecessary energy consumption.

Built in Wi-Fi

As well as having an Ethernet and LAN ports you can wirelessly connect to the internet thanks to the built in Wi-Fi.



Long Life Industrial Display

Designed for use in commercial applications this screen can run 24/7. There are no external buttons or controls to avoid tampering.

Front Protection Glass

Provides additional protection against physical impact during use. 4 mm extra clear tempered protection glass provides additional protection against physical impact during use.

Powerful Body Structure

It has a IP65 class protection body design that has wide humidity range, against dust filler, fan and weather resistant. 2 mm galvanized electrostatic powder application to the sheet surface having long lasting and durable body.

Rich Entegration System

It has the infrastructure that can work seamlessly with Windows and Android platforms.

Audio

Optional integrated speaker also has an audio out port for connecting headphones or external speakers.

Optional Touch Technology

The most popular interactive applications durable and reliable touch technology for ease of use.

Branding and Color Applications

Provides you to highlight your corporate identity with unique color and logo application.

Pop-Up Cover Design

The product has a hinged lid made of 2 mm galvanized sheet metal. In addition to protecting display from environment condition, is also facilities technical interventions.

Safe and Easy Application

You can make safe application in every area with the fixed foot structure designed for ease of use. (M10 tij)

PANEL	TO550XQ-P	TO650XQ-P	TO750XQ-P	TO850XQ-P
Panel Size	55"	65"	75"	85"
Panel Type	60Hz ELED, (a-Si TFT-LCD , LCM)	60Hz ELED, (a-Si TFT-LCD , LCM)	60Hz ELED, (a-Si TFT-LCD , LCM)	60Hz ELED, (a-Si TFT-LCD , LCM)
Resolution	3840 x 2160	3840 x 2160	3840 x 2160	3840 x 2160
Active Display Area (mm)	1209,6 x 680,4	1431,4 x 806,5	1650,24 x 928,26	1872 x 1053
Brightness (Typ.)	500 cd/m ²	500 cd/m ²	500 cd/m ²	500 cd/m ²
Contrast	4000:1 (Typ.) (TM)	4000:1 (Typ.) (TM)	5000:1 (Typ.) (TM)	5000:1 (Typ.) (TM)
Viewing Angle (H x V)	178° x 178°	178° x 178°	178° x 178°	178° x 178°
Response Time (G-to-G)	8 ms	8 ms	8 ms	8 ms
Frame Design	Angular	Angular	Angular	Angular
Applications	Horizontal/Vertical	Horizontal/Vertical	Horizontal/Vertical	Horizontal/Vertical

PANEL CONNECTIVITY

Video Input	DVI/HDMI 1,2,3/DP 1,2	DVI/HDMI 1,2,3/DP 1,2	DVI/HDMI 1,2,3/DP 1,2	DVI/HDMI 1,2,3/DP 1,2
Video Output	N/A	N/A	N/A	N/A
Audio Input / Output	Stereo mini Jack	Stereo mini Jack	Stereo mini Jack	Stereo mini Jack
External Control	RS232, (IR)	RS232, (IR)	RS232, (IR)	RS232, (IR)
External Sensor (optional)	Temperature sensor, Light Sensor	Temperature sensor, Light Sensor	Temperature sensor, Light Sensor	Temperature sensor, Light Sensor

POWER

Power Type	Internal	Internal	Internal	Internal
Power Requirement	AC 100 - 240 V~ (+/- 10 %), 50/60 Hz	AC 100 - 240 V~ (+/- 10 %), 50/60 Hz	AC 100 - 240 V~ (+/- 10 %), 50/60 Hz	AC 100 - 240 V~ (+/- 10 %), 50/60 Hz
Power Consumption	395W	495W	615W	615W
Standby Mode	<0,5W	<0,5W	<0,5W	<0,5W

DIMENSIONS

Product size(mm)	850 x 1900 x 150	2000 x 850 x 150	2100 x 980 x 150	2100 x 980 x 150
Package Size (mm)	950 x 2000 x 250	2100 x 950 x 250	2200 x 1080 x 250	2200 x 1080 x 250
Product Weight (kg)	23Kg	32.6kg	30kg	30kg
Package Weight (kg)	27Kg	38.1kg	39kg	39kg

OPERATION

Operation Life	7/24 - 50.000 hours	7/24 - 50.000 hours	7/24 - 50.000 hours	7/24 - 50.000 hours
Working Conditions	Operation Temp.:0~ 50 °C ; Storage Temp.: -30~60 °C	Operation Temp.:0~ 50 °C ; Storage Temp.: -30~60 °C	Operation Temp.:0~ 50 °C ; Storage Temp.: -30~60 °C	Operation Temp.:0~ 50 °C ; Storage Temp.: -30~60 °C
Humidity	10 ~ 80%	10 ~ 80%	10 ~ 80%	10 ~ 80%

CERTIFICATION AND COMPATIBILITY

Safety	EN60950-1	EN60950-1	EN60950-1	EN60950-1
EMC	Class A	Class A	Class A	Class A
Environment	ENERGY STAR 6.0 (USA)	ENERGY STAR 6.0 (USA)	ENERGY STAR 6.0 (USA)	ENERGY STAR 6.0 (USA)

OPTIONAL ACCESSORIES

Touch Overlay, Protection Glass Overlay, Protection Glare Overlay, Logo Overlay

OTHER

Included in Pocket | Easy Installation Guide, Warranty Document, Power Cable (Other Accessories Externally)

PANEL	TO550XQ-P	TO650XQ-P	TO750XQ-P	TO850XQ-P
Panel Size	55"	65"	75"	85"
Panel Type	60Hz ELED, (a-Si TFT-LCD , LCM)	60Hz ELED, (a-Si TFT-LCD , LCM)	60Hz ELED, (a-Si TFT-LCD , LCM)	60Hz ELED, (a-Si TFT-LCD , LCM)
Resolution	3840 x 2160	3840 x 2160	3840 x 2160	3840 x 2160
Active Display Area (mm)	1209,6 x 680,4	1431,4 x 806,5	1650,24 x 928,26	1872 x 1053
Brightness (Typ.)	500 cd/m ²	500 cd/m ²	500 cd/m ²	500 cd/m ²
Contrast	4000:1 (Typ.) (TM)	4000:1 (Typ.) (TM)	5000:1 (Typ.) (TM)	5000:1 (Typ.) (TM)
Viewing Angle (H x V)	178° x 178°	178° x 178°	178° x 178°	178° x 178°
Response Time (G-to-G)	8 ms	8 ms	8 ms	8 ms
Frame Design	Angular	Angular	Angular	Angular
Applications	Horizontal/Vertical	Horizontal/Vertical	Horizontal/Vertical	Horizontal/Vertical

PANEL CONNECTIVITY				
Video Input	DVI/HDMI 1,2,3/DP 1,2	DVI/HDMI 1,2,3/DP 1,2	DVI/HDMI 1,2,3/DP 1,2	DVI/HDMI 1,2,3/DP 1,2
Video Output	N/A	N/A	N/A	N/A
Audio Input / Output	Stereo mini Jack	Stereo mini Jack	Stereo mini Jack	Stereo mini Jack
External Control	RS232, (IR)	RS232, (IR)	RS232, (IR)	RS232, (IR)
External Sensor (optional)	Temperature sensor, Light Sensor	Temperature sensor, Light Sensor	Temperature sensor, Light Sensor	Temperature sensor, Light Sensor

POWER				
Power Type	Internal	Internal	Internal	Internal
Power Requirement	AC 100 - 240 V~ (+/- 10 %), 50/60 Hz	AC 100 - 240 V~ (+/- 10 %), 50/60 Hz	AC 100 - 240 V~ (+/- 10 %), 50/60 Hz	AC 100 - 240 V~ (+/- 10 %), 50/60 Hz
Power Consumption	395W	495W	615W	615W
Standby Mode	<0,5W	<0,5W	<0,5W	<0,5W

DIMENSIONS				
Product size(mm)	850 x 1900 x 150	2000 x 850 x 150	2100 x 980 x 150	2100 x 980 x 150
Package Size (mm)	950 x 2000 x 250	2100 x 950 x 250	2200 x 1080 x 250	2200 x 1080 x 250
Product Weight (kg)	23Kg	32.6kg	30kg	30kg
Package Weight (kg)	27Kg	38.1kg	39kg	39kg

OPERATION				
Operation Life	7/24 - 50.000 hours	7/24 - 50.000 hours	7/24 - 50.000 hours	7/24 - 50.000 hours
Working Conditions	Operation Temp.:0~ 50 °C ; Storage Temp.: -30~60 °C	Operation Temp.:0~ 50 °C ; Storage Temp.: -30~60 °C	Operation Temp.:0~ 50 °C ; Storage Temp.: -30~60 °C	Operation Temp.:0~ 50 °C ; Storage Temp.: -30~60 °C
Humidity	10 ~ 80%	10 ~ 80%	10 ~ 80%	10 ~ 80%

CERTIFICATION AND COMPATIBILITY				
Safety	EN60950-1	EN60950-1	EN60950-1	EN60950-1
EMC	Class A	Class A	Class A	Class A
Environment	ENERGY STAR 6.0 (USA)	ENERGY STAR 6.0 (USA)	ENERGY STAR 6.0 (USA)	ENERGY STAR 6.0 (USA)

OPTIONAL ACCESSORIES				
Touch Overlay, Protection Glass Overlay, Protection Glare Overlay, Logo Overlay				

OTHER				
Included in Pocket	Easy Installation Guide, Warranty Document, Power Cable (Other Accessories Externally)			



unisigns



unisigns



unisigns



unisign

www.unisign.com.tr

info@unisign.com.tr



TOTEM

Elegance P Series