



www.unisign.com.tr www.unisign.com.fr

DESK

Active Series

Create impressive space for all target audiance

Deliver an Exclusive Experience

Digital Desk is a completely customizable multi-touch solution that meets all users' expectations, from customers and guests, to senior executives and students. For more effective communication with customers, visitors, students, staff, or guests.



1

Digital Desk touch screens are the best and most popular solution!

With Digital Desk screens, you can share a wide range of information and visual resources on horizontal screen surfaces, generating interaction.



Areas of Usage: Shopping Center, Hospital, Banks, Education, Hotels, Cinema, Restaurant, Fair, Gallery, Entertainment, Bus/Train Stations



OTHER

Included in Packet



PANEL	KD320MA-AI	KD430MA-AI	KD490MA-AI	KD550MA-AI
Panel Size	31,5"	43"	49"	55"
Panel Type	60Hz ELED	60Hz ELED	60Hz ELED	60Hz ELED
Resolution	1920 X 1080	1920 X 1080	1920 X 1080	1920 X 1080
Brightness (Typ.)	400 cd/m ²	500 cd/m ²	500 cd/m ²	500 cd/m ²
Contrast	3000:1 (Typ.) (TM)	3000:1 (Typ.) (TM)	3000:1 (Typ.) (TM) 178° x 178°	3000:1 (Typ.) (TM)
Viewing Angle (H x V) Response Angle (G-to-G)	178° x 178° 8 ms (G to G)	178° x 178° 8 ms (G to G)	8 ms (G to G)	178° x 178° 8 ms (G to G)
Active Display Area (mm)	698,4(H) x 392,85(V)	940,89(H) x 529,25(V)	1073,779(H) x 604(V)	1209,6(H) x 680,4(V)
PANEL CONNECTIVITY				
Video Input	VGA, HDMI, DVI	VGA, HDMI, DVI	VGA, HDMI, DVI	VGA, HDMI, DVI
/ideo Output	N/A	N/A	N/A	N/A
Audio Input / Output	Stereo mini Jack	Stereo mini Jack	Stereo mini Jack	Stereo mini Jack
JSB	N/A	N/A	N/A	N/A
	N/A	N/A	N/A	N/A
Internal Control	IV/A	N/A	IN/A	IN/A
POWER				
Power Type	Adapter	Adapter	Adapter	Adapter
Power Requirement	AC 100 - 240 V~ (+/- 10 %), 50/60 Hz	AC 100 - 240 V~ (+/- 10 %), 50/60 Hz	AC 100 - 240 V~ (+/- 10 %), 50/60 Hz	AC 100 - 240 V~ (+/- 10 %), 50/60 Hz
Power Consumption	88W	154W	165W	190W
Standby Mode	<0,5W	<0,5W	<0,5W	<0,5W
DIMENSIONS				
Product Size(mm) (w x h x d)	1110 x 832 x 525	1110 x 1067 x 635	1150 x 1160 x 680	1300 x 1330 x 800
Package Size (mm)	1300 x 900 x 600	1300 x 1100 x 700	1300 x 1200 x 750	1400 x 1400 x 850
Product Weight(kg)	54	60	65	70
Package Weight(kg)	63	67	75	83
OPERATION				
Operation Life	7/24 - 50.000 hours			
	Operation Temp.:0~ 40 °C ;	Operation Temp.:0~ 40 °C;	Operation Temp.:0~ 40 °C ;	Operation Temp.:0~ 40 °C;
Norking Conditions	Storage Temp.:-20~60 °C	Storage Temp.:-20~60 °C	Storage Temp.:-20~60 °C	Storage Temp.:-20~60 °C
Humidity	10 ~ 80%	10 ~ 80%	10 ~ 80%	10 ~ 80%
CERTIFICATION AND C	COMPATIBILITY			
Safety	EN60950-1	EN60950-1	EN60950-1	EN60950-1
EMC	Class A	Class A	Class A	Class A
Environment	ENERGY STAR 6.0 (USA)			
OPTIONAL ACCESSOR	RIES			
	Barcode, NFC, RFID. Beac	on, Bluetooth, Camera, Pin Pad,	Industrial Kevboard, Receipt	

Easy Installation Guide, Warranty Document, Power Cable (Other Accessories Externally)

Optional Wireless Connections Front Protection Glass It has the Bluetooth, NFC and RFID It is manufactured from glass that is reinforced by chemical processes and is resistant to very high piercing. Provides additional protection against phy-Built in Wi-Fi sical impact during use. As well as having an Ethernet and LAN ports you can wirelessly connect to the 0000 internet thanks to the built in Wi-Fi. 120307 Long Life Industrial Display Designed for use in commercial applications this screen can run 24/7. There are no external buttons or controls to avoid tampering. **Touch Tehcnology** The most popular interactive applications durable and reliable touch techno-Audio logy for ease of use. Optional integrated speaker also has an audio out port for connecting headphones or external speakers. Branding and Color Applications Provides you to highlight your corporate identity with unique color and logo application. **Rich Entegration System** It has the infrastructure that can work Application Specific Design seamlessly with Windows and Android platforms. Designed with discreet retractable casters for easy manoeuvrability. Depen-Accessories ding on where you are positioning, spe-Barcode Reader, NFC, RFID, Beacon, cial foot design can be made. Bluetooth, Pin Pad, Camera, Industrial Keyboard, Receipt Printer, Audio System, Glass Protector, Mirror Protec-

tor, Glass Logo, Colorful Glass

OTHER

Included in Packet



PANEL	KD320EA-BI	KD430EA-BI	KD490EA-BI	KD550EA-BI
anel Size	31,5"	43"	49"	55"
anel Type	60Hz ELED	60Hz ELED	60Hz ELED	60Hz ELED
esolution	1920 X 1080	1920 X 1080	1920 X 1080	1920 X 1080
ightness (Typ.)	400 cd/m ²	500 cd/m²	500 cd/m ²	500 cd/m²
ontrast	3000:1 (Typ.) (TM) 178° x 178°			
ewing Angle (H x V) esponse Angle (G-to-G)	8 ms (G to G)			
etive Display Area (mm)	698,4(H) x 392,85(V)	940,89(H) x 529,25(V)	1073,779(H) x 604(V)	1209,6(H) x 680,4(V)
ANEL CONNECTIVITY				
deo Input	VGA, HDMI, DVI	VGA, HDMI, DVI	VGA, HDMI, DVI	VGA, HDMI, DVI
deo Output	N/A	N/A	N/A	N/A
udio Input / Output	Stereo mini Jack	Stereo mini Jack	Stereo mini Jack	Stereo mini Jack
SB	N/A	N/A	N/A	N/A
ternal Control	N/A	N/A	N/A	N/A
ternal control	NA	IV/A	IVA	[NA
OWER				
ower Type	Adapter	Adapter	Adapter	Adapter
ower Requirement	AC 100 - 240 V~ (+/- 10 %), 50/60 Hz	AC 100 - 240 V~ (+/- 10 %), 50/60 Hz	AC 100 - 240 V~ (+/- 10 %), 50/60 Hz	AC 100 - 240 V~ (+/- 10 %), 50/60
ower Consumption candby Mode	88W <0,5W	154W <0,5W	165W <0,5W	190W <0,5W
anaby wode	<0,3vv		<0,5W	\\\\\\\\
IMENSIONS				
roduct Size(mm) (w x h x d)	1150 x 870 x 525	1200 x 1100 x 635	1200 x 1190 x 680	1380 x 1378 x 832
ackage Size (mm)	1250 x 920 x 575	1300 x 1250 x 625	1300 x 1250 x 730	1480 x 1428 x 860
oduct Weight(kg)	54	60	66	70
ackage Weight(kg)	63	67	74	78
PERATION				
peration Life	7/24 - 50.000 hours			
orking Conditions	Operation Temp.:0~ 40 °C ; Storage Temp.:-20~60 °C			
umidity	10 ~ 80%	10 ~ 80%	10 ~ 80%	10 ~ 80%
ERTIFICATION AND C	OMPATIBILITY			
afety	EN60950-1	EN60950-1	EN60950-1	EN60950-1
MC	Class A	Class A	Class A	Class A
nvironment	ENERGY STAR 6.0 (USA)			
PTIONAL ACCESSOR	IES	,		

Easy Installation Guide, Warranty Document, Power Cable (Other Accessories Externally)











www.unisign.com.tr info@unisign.com.tr

